



TIP	PRETOK [cc]	PRETOK		MAX KONSTANTNI TLAK [bar]	MAX VRTLJAJI [vrt/min]	DIMENZIJE		NOTRANJE DIMENZIJE			ZUNANJE DIMENZIJE		
		pri 1500 vrt/min [lit/min]	pri max. vrtljajih			A [mm]	B [mm]	E	F	d	E	F	d
20A4,5X066	4,5	6,14	14,33	250	3500	40,5	78	30,2	13,1	M6-6H	30,2	13,1	M6-6H
20A8,2X066	8,2	11,32	26,40	250	3500	43,5	83,9	30,2	13,1	M6-6H	30,2	13,1	
20A12X066	12	16,92	39,48	250	3500	46,6	90,3	39,7	19	M8-6H	30,2	14,2	
20A16X066	16	23,04	38,40	250	2500	50	96,6	39,7	19	M8-6H	30,2	14,2	
20A19X066	19	27,36	45,60	200	2500	52	101,5	39,7	19	M8-6H	30,2	14,2	
20A22X066	22	31,68	42,24	180	2000	55	106,5	39,7	19	M8-6H	30,2	14,2	
20A25X066	25	36,00	48,00	160	2000	57,2	111,4	39,7	19	M8-6H	39,7	19	M8